

All Weather Speaker

IP55 

MAIN APPLICATIONS

- Theme and Amusement parks
- Outdoor Entertainment centers
- Multipurpose indoor / outdoor venues
- Background music
- Athletic fields
- Swimming pools
- Convention centers
- Cruise ship
- Stadiums / Arenas

MAIN FEATURES

- Multipurpose 5" full-range 120W - 8Ohm / 112dB SPL
- 2 way configuration with an high power 5" cone
- 1" dome for high frequencies
- 100V line transformer with selectable 50W power tapping
- Die-cast aluminium wall bracket with ball-socket for multi-angle adjustment capability, with a security cable
- 4 wires cable to select the desired power tapping
- Water-stop grille with 3 layers of protection
- IP55 weather resistant
- Standard grey finish RAL 7011



DESCRIPTION

The FBT SHADOW 105T is a weatherproof two way loudspeaker system designed to provide high quality voice and music reproduction in applications requiring extreme weather resistance. It is designed to withstand long-term exposure to tough, environmental conditions. The low frequency transducer is a 5" woofer with a 1" voice coil. The FBT SHADOW 105T features a line transformer for 100V applications with selectable power tapping. The cabinet is a single piece rotational moulded in polyethylene, fully UV protected. The cabinet is equipped with a die cast aluminium wall bracket with ball-socket for multi angle adjustment capability. The FBT SHADOW 105T meets the requirements of IP55 code (International Protection Rating).

TECHNICAL SPECIFICATIONS

GENERAL

Code	RAL 7011	36192
Configuration	way	2
Low frequency woofer	inch	5 - 1 coil
High frequency driver	inch	1 dome
Transformer	V / W	100 / 50

ACOUSTIC SPECIFICATIONS

Frequency response (@-6dB)	Hz	90 - 20k
Sensitivity (@1W/1m)	dB	89
MAX SPL (cont/peak)	dB	109 / 112
Dispersion	H° x V°	100
Crossover frequency	Hz	3k
Recommended HP filter	Hz - dB oct	70 - 24

INPUTS & OUTPUTS

Input connectors		4 wire cable
------------------	--	--------------


AMPLIFIER

Recommended amplifier	W RMS	120
Long term power	W	60
Short term power (IEC 268-5)	W	240
Nominal impedance	Ohm	8
Transformer taps	W	50 / 40 / 25 / 15


MECHANICAL SPECIFICATIONS

Material	Cabinet	Polystyrene
	Grille	Aluminium
Net dimensions (WxHxD)	mm	168 x 222 x 161
	inch	6.61 x 8.74 x 6.33
Transport dimensions (WxHxD)	mm	258 x 300 x 235
	inch	10.15 x 11.81 x 9.25
Net weight	kg	3.10
	lb	6.83
Transport weight	kg	3.60
	lb	7.93


DIMENSIONAL DRAWING




CONTROL PANEL



HORIZONTAL POLAR DIAGRAM



FREQUENCY RESPONSE DIAGRAM



VERTICAL POLAR DIAGRAM

