

Touch Screen Microphone Station

MAIN FEATURES

- Emergency key
- "Key pad" mode / "Numeric pad" mode
- Functions keys to create groups of zones
- Zone labels customization
- Live emergency calls
- Broadcast calls
- Status LEDs / Fault signaling LEDs
- Pre-recorder messages recall
- Emergency messages reset
- Warning signal muting

DESCRIPTION

The TSC 6000 / EN touch screen remote unit allows the sending of emergency live messages and evacuation/alert pre-recorded messages. The unit is equipped with a 7" touch screen back-lighted display for zones selection and customization, while a group of LEDs give information about the emergency system state and faults.



EN 54-16:2008

EN 54-16:2008
Cert. Nr. 0068-CPR-044/2016

Declaration of Performance (DoP)
available on the website: www.fbt.it

TECHNICAL SPECIFICATIONS

GENERAL

Code		40951
No of selectable zones		1 ÷ 216 from 20 to 60 zone selection keys, +6 function keys
Typical output level	mV	300

ACOUSTIC SPECIFICATIONS

Frequency response	Hz	20 ÷ 20k
Distortion		< 1%
LOW CUT filter	dB/Hz	-10 / 100
S/N Ratio	dB	> 60

INPUTS & OUTPUTS

Connection		RJ45 (IN/OUT)
------------	--	---------------

POWER SUPPLY

Power supply voltage	Vcc	24
MAX absorption @24Vcc	mA	165

MECHANICAL SPECIFICATIONS

Net dimensions (WxHxD)	mm inch	230 x 80 x 200 9.05 x 3.14 x 7.87
Net weight	kg lb	1.61 3.54